

## **GIXXER SERIES SPECIFICATIONS**

Engine	
Engine Type:	4-Stroke, 1-Cylinder, Air-cooled
Valve System:	SOHC, 2 Valve
Displacement:	154.9 cm <sup>3</sup>
Bore x Stroke:	56.0 mm x 62.9 mm
Engine Output:	14.8ps@8000rpm
Torque:	14Nm@6000rpm
Fuel System:	Gixxer SF: FI (Fuel Injection)
	Gixxer: Carburettor
Starter System:	Gixxer SF: Electric (FI)
	Gixxer: Electric/Kick
Transmission Type:	5 Speed, MT
Transmission Type.	o opoda, mi

Dimensions and Weight		
Wheels:	Cast	
Overall Length:	2050 mm	
Overall Width:	785 mm	
Overall Height:	Gixxer SF: 1085 mm	
	Gixxer: 1030 mm	
Wheel Base:	1330 mm	
Ground Clearance:	160 mm	
Seat Height:	780 mm	
Kerb Mass:	Gixxer SF: 140 kg	
	Gixxer: 136 Kg	
Fuel Tank:	12 L	

Suspension		
Front:	Telescopic	
Rear:	Swing Arm, Mono Suspension	
Tyre Si	ize	
Front:	100/80 - 17 - <b>Tubeless</b>	
Rear:	140/60R - 17 - <b>Radial Tubeless</b>	
Brake		
Front:	Disc	
Rear:	Disc	

Ride safe. Wear a helmet. | Prices of the vehicles are available on our website

<b>Electrical</b>	
attery:	Maintenance free 12V, 3Ah
eadlight:	12 V 35/35 W
ail light:	LED
The state of the state of	

## JD Power Awards

The Suzuki Gixxer/ Gixxer SF was the highest ranked Upper Executive Motorcycle in the J.D. Power 2018 India Two-Wheeler Initial Quality Study (2WIQS) Study™ based on evaluations from 10,102 vehicle owners who purchased a new vehicle between March 2017 and October 2017. The study includes 88 two-wheeler models from ten makes. The Suzuki Gixxer/ Gixxer SF was also the highest ranked Upper Executive Motorcycle in the J.D. Power 2018 India Two-Wheeler Automotive Performance, Execution and Layout (2WAPEAL) Study™ based on evaluations from 9,981 vehicle owners who purchased a new vehicle between March 2017 and October 2017. The study includes 88 two-wheeler models from ten makes. Study results are based on experiences and perceptions of owners surveyed. Your experiences may vary. Visit india.jdpower.com.







#Including 3 Yea optional warrant

Visit us at: www.suzukimotorcycle.co.in 👍 /Suzuki2wheelers 📢 /amGixxer You Tube /Suzuki2wheelers 💟 /Suzuki2wheelers 👩 /Suzuki2wheelers

Specifications, appearances, equipments, colours, materials and other items of Suzuki product shown in this leaflet are subject to change by manufacturers at any time without notice and they may vary depending upon local conditions and requirements. Please visit your local dealer for details of any changes. Actual body colour may differ from the colours in this leaflet. \*ABS is not designed to shorten the braking distance. ABS cannot prevent wheel skidding caused by braking while cornering. Please ride carefully and do not overly rely on ABS.

Regd, Office, Sales & Marketing Office: 2nd Floor, Plot No. 1, Nelson Mandela Road, Vasant Kunj, New Delhi - 110 070. Fax: 011-4607 5418.





ABS\* (Anti-lock brake system). a supplemental system, which automatically controls the braking force efficiently & avoids wheels locking up due to slippery road, sudden change of road conditions or excessive braking in a certain controllable range. Please do not overly rely on ABS.

**EDXER** 



The Gixxer SF now comes with advanced Fuel Injection Technology equipped with 6 sensors to calculate the optimum amount of fuel to be injected for better combustion efficiency. Thereby improving fuel efficiency and providing accurate throttle response at all rpm to make your every ride even more exciting.



SEP (Suzuki Eco Performance) is a new developmental concept proposed by Suzuki. At Suzuki, we pay great attention to riding performance, and "SEP" stands for our next-generation engine that offers both low fuel consumption and superior acceleration.

















Smart digital Instrumentation with Gear position and RPM indicator





Clear lens LED tail lamp